Coordinate-Time Synchronization Architecture for Multi-Planetary Civilizations: A Dual-Clock Framework with Relativistic Two-Way Time Transfer

A Theoretical and Engineering Analysis

Covering forward and reverse dilation budgets, mission-class feasibility analysis under chemical-propulsion constraints, and a synchronization protocol for static colonies and ships in transit

April 2026

Abstract

We present a complete architectural treatment of clock synchronization across an emerging multi-planetary civilization, integrating relativistic time-dilation analysis with practical engineering protocols. The work is organized in three parts. Part I quantifies the forward and reverse time-dilation budgets achievable with current and near-term technology, demonstrating that with chemical propulsion and gravity assists a 1 kg payload can accumulate at most ~470 ms of forward dilation per mission-year (peak ~10 s for idealized circular orbits at the Parker Solar Probe thermal limit), while the reverse direction is fundamentally bounded at ~489 ms/yr by Earth's own dilation budget. Part II analyzes a three-twin scenario in which two probes flying opposing trajectories accumulate up to ~16 seconds of mutual offset over a 50-year mission. Part III develops a dual-clock synchronization architecture with civil time (proper time, for biology and daily life) and coordinate time (Barycentric Coordinate Time, TCB, for inter-node communication), connected via Relativistic Two-Way Time Transfer (RTWTT) with Shapiro-delay corrections. We show that the same architecture extends naturally from static colonies (Earth, Moon, Mars, Titan) to ships in transit through a Kalman-filter-based joint estimation of position, velocity, and clock offset, achieving ~1 ns synchronization precision when position knowledge is meter-scale. The framework is principled, presently feasible, and reduces multi-planet timekeeping to ordinary engineering once general-relativistic effects are accepted as known parameters rather than obstacles.

1. Introduction

Time, on Earth, has historically been a single shared phenomenon. The various time scales used in practice (UTC, TAI, GPS Time, TT, TCG, TCB) differ by amounts that are nearly invisible to civil life, and their relationships are well-defined by IAU resolutions originally drafted for astronomical convenience rather than human necessity. This is no longer a sustainable framing.

Active programs at NASA, ESA, and the China National Space Administration are constructing the first non-terrestrial coordinate time scale: Coordinated Lunar Time (LTC), targeted for definition by 2026 in response to a White House directive issued in April 2024. Permanent human presence on Mars within the next two decades is a stated goal of multiple programs. Outer-system exploration of Titan, Europa, and other targets follows naturally. Each of these locations occupies a different point in the Sun's gravitational potential and moves with a different velocity vector through the solar system, with the result that local atomic clocks at each location tick at measurably different rates.

The engineering challenge is no longer hypothetical. Two locked atomic clocks, one on Earth and one on the Moon, drift apart by approximately 58.7 microseconds per Earth day; on Mars

the figure exceeds 489 microseconds per day; on Titan, ~1.16 milliseconds per day. Without active correction, distributed systems spanning these locations would lose causal ordering within hours, navigation fixes would degrade by kilometers, and inter-node protocols designed for Earth-bound networks would simply fail.

This paper develops a complete framework for multi-planet timekeeping. We begin with the underlying physics of time dilation in the solar system, establishing what is achievable with present propulsion technology and what fundamental limits apply. We then build the engineering architecture: a dual-clock system at every node that separates local civil time (driven by local proper time, anchored to local rotation) from coordinate time (TCB, used for all inter-node communication). Finally, we extend this architecture to ships in transit and analyze its precision under realistic conditions.

The result is, we believe, the right architecture: principled, presently buildable, and gracefully scalable from Earth-Moon to interstellar distances with no change in underlying principles.

2. Time Dilation in the Solar System

2.1 The two channels of dilation

General relativity provides two independent mechanisms by which a clock's tick rate, measured against a coordinate time, may differ from its proper rate:

- Kinematic dilation: a moving clock ticks slowly relative to coordinate time by the Lorentz factor.
- Gravitational dilation: a clock at lower gravitational potential (deeper in a well) ticks slowly relative to one at higher potential.

To leading order in v^2/c^2 and φ/c^2, the slowdown of a clock at position r with velocity v, relative to TCB (a clock notionally at rest at the solar system barycenter free from any gravity well), is:

$$S(t) = \sum GM_i / (r_i\, c^2) \;+\; (1/2)\, v^2 / c^2$$

where the sum runs over all gravitating bodies whose potentials affect the clock location. For most solar-system applications, the Sun dominates the gravitational term, with smaller contributions from the host planet and any orbiting satellite.

2.2 Slowdown factors at present and prospective colonies

Applying the formula to four locations of immediate engineering interest yields the following slowdown rates relative to TCB:

Location	Slowdown vs TCB (ppb)	Drift per day	Drift per year
Earth surface	15.50	1339 μs	489 ms
Moon surface	14.85	1283 μs	469 ms

Mars surface	9.84	851 μs	311 ms
Titan surface	2.03	175 μs	64 ms

Table 1. Clock slowdown at each location relative to TCB. The Earth–Moon difference of 0.65 ppb yields the well-known ~57 μs/day rate, consistent with NASA's published figure of 58.7 μs/day for the Moon–TT differential.

Three observations are immediate. First, every colony's slowdown is dominated by either the Sun's potential (outer locations) or the host planet's velocity (inner locations); local surface gravity contributes a fixed offset of order 1 ppb on rocky worlds. Second, the differences between colonies are dimensionally small (parts per billion) but cumulatively large (hundreds of milliseconds per year). Third, no two surface locations agree on time at the precision required for nanosecond-class navigation; active synchronization is mandatory.

3. Maximum Forward Dilation: A Mission-Class Analysis

We now ask: given current technology, how much time dilation can be accumulated by a payload over a defined mission? The constraints are: 1 kg payload, chemical propulsion only (specific impulse ≤ 450 s), gravity assists permitted, return to Earth required. We treat both human-survivable and pure machine missions.

3.1 Pure kinematic dilation

Constant-acceleration solutions to the relativistic rocket equation give, for proper acceleration a sustained over proper time τ:

$$\gamma = \cosh(a\tau/c), \quad t\_coord = (c/a)\sinh(a\tau/c)$$

At human-tolerable 1 g sustained for one proper year, the final Lorentz factor is γ ≈ 1.58, and elapsed Earth time is approximately 1.19 years — a forward dilation of about two months. At 10 g (machine territory), γ reaches ~1500 and elapsed Earth time is ~1500 years. These figures, however, vastly exceed the Δv achievable with chemical propulsion: a Saturn V class vehicle delivering a 1 kg payload achieves at most ~30 km/s of usable Δv in deep space, corresponding to $v/c \approx 10^{-4}$ and $\gamma - 1 \approx 5 \times 10^{-9}$. Kinematic dilation is therefore negligible under our constraints.

3.2 Gravitational dilation: Sun-grazing orbits

The dominant achievable dilation channel is gravitational. The maximum sustainable proximity to the Sun is set by thermal protection: the Parker Solar Probe demonstrates 9.86 R⊙ (~6.86×10^6 km from Sun center) as the current technological limit. At this radius, the gravitational slowdown factor for a circular orbit is:

$$S = 3\,GM_\odot / (2\,r\,c^2) \approx 3.23 \times 10^{-7} = 10.2 \text{ seconds per year}$$

However, no chemical-propulsion mission can circularize at 9.86 R⊙. A realistic Sun-grazer with perihelion at 9.86 R⊙ and aphelion sufficient to complete one orbit per year (semimajor axis ~1

AU) spends almost all its time near aphelion (Kepler's second law). Time-averaging the dilation factor over such an elliptical orbit yields a per-mission-year forward dilation of approximately 467 ms — about a factor of 22 below the idealized circular case.


Time dilation accumulation: probe time vs Earth time
1e6
Extra Earth time accumulated (milliseconds)
Mission time (proper time, years)
Parker-class orbit (peri 9.86 R_sun, apo 2 AU)
Tighter Parker (peri 9.86 R_sun, apo 50 R_sun)
Idealized circular at 9.86 R_sun
Extreme: circular at 3 R_sun (impossible)
1 yr
Same data, log-log scale
Extra Earth time (seconds) [log]
Mission time (proper time, years) [log]
Saturn V max mission (~50 yr)

Figure 1. Forward time dilation accumulation versus mission duration for several orbital scenarios. Linear (left) and log–log (right) views. The realistic chemical-propulsion regime accumulates ~0.5 s per year of mission proper time; idealized circular orbits at the Parker thermal limit reach ~10 s/yr but require propellant beyond chemical capability.

3.3 Saturn V–class mission ceiling

The maximum mission duration is set by power: a radioisotope thermoelectric generator using Pu-238 (half-life 87.7 years) can sustain a 1 kg solid-state payload for approximately 50–60 years. Voyager 1, launched in 1977, has sustained operation for ~49 years and provides empirical confirmation. Over a 50-year realistic Sun-grazing mission, total forward dilation is ~23.4 seconds; the idealized circular case extends to ~509 seconds (~8.5 minutes). These represent the upper bounds of what is presently achievable.

4. The Reverse Direction: Negative Dilation

We now examine the symmetric question: can a probe age more than Earth, returning to find that less time has passed at home? We emphasize at the outset that this is not backward time travel — both clocks tick forward, and the probe simply accumulates more proper time. Genuine retrograde time travel requires closed timelike curves, which are inaccessible to any classical propulsion technology.

4.1 The mechanism

Earth itself is not a stationary, gravity-free reference. The Earth surface clock is slowed relative to TCB by three contributions:

- Sun's gravitational potential at 1 AU: 9.87 ppb
- Earth's 30 km/s orbital velocity: 4.93 ppb

- Earth's own surface gravity: 0.70 ppb

A probe placed at higher gravitational potential (farther from the Sun) and lower velocity (less heliocentric speed) will tick faster than Earth, recovering some or all of Earth's 15.5 ppb dilation budget.

4.2 The hard ceiling

The maximum recoverable amount is bounded by Earth's total slowdown vs a stationary observer at infinity: 15.5 ppb, equal to ~489 ms per year of probe proper time. No classical mechanism can exceed this limit — there is no clock anywhere in the solar system that ticks faster than one at rest at infinity.


Positive vs Negative Dilation
+ Realistic Sun-grazer (peri 9.86 R_sun, apo 2 AU)
+ Idealized circular at 9.86 R_sun
− Earth-Mars ellipse
− Earth-Jupiter ellipse
− Voyager-like (1-100 AU)
− Idealized: rest at infinity
Earth time − Probe time (milliseconds)
Mission duration (probe proper years)
Earth ages MORE
(forward time travel)
Probe ages MORE
(negative time travel)
Magnitude comparison (log-log)
50-yr negative limit (24.5 s)
|Earth − Probe time| (milliseconds) [log]
Mission duration (probe proper years) [log]

Figure 2. Comparison of forward and negative dilation rates for several mission profiles. The forward direction (solid lines) is unbounded in principle, limited only by propulsion energy budget. The negative direction (dashed lines) saturates at ~489 ms/yr regardless of mission profile.

4.3 Practical reverse missions

A 1 kg probe launched into a high-aphelion orbit can recover a significant fraction of the theoretical limit:

Orbital profile	Period	Reverse rate (ms/yr)
Earth–Mars ellipse (1–1.52 AU)	1.4 yr	118
Earth–Jupiter ellipse (1–5.2 AU)	5.5 yr	338
Earth–Saturn ellipse (1–9.5 AU)	12 yr	400
Voyager-class (1–100 AU)	359 yr	480
Idealized: at rest at infinity	—	489

Table 2. Reverse dilation rates for orbital profiles accessible to chemical propulsion plus gravity assists. The Voyager-class profile asymptotically approaches the theoretical bound but at orbital periods exceeding mission lifetime.

5. Mutual Dilation Between Opposing Probes

A natural extension is to fly two probes simultaneously: one Sun-ward (forward dilation) and one outward (reverse dilation). When the probes reunite, what is their mutual offset?

5.1 The principle: dilation is additive through coordinate time

Each probe's clock ticks at a known rate relative to TCB. If clock A loses X ms/yr and clock B gains Y ms/yr relative to Earth, then A and B differ by (X + Y) per year, not |X − Y|. The mutual offset between two probes flying opposite trajectories therefore exceeds either probe's individual offset against Earth.

5.2 Worked case

Probe A: Sun-grazer with perihelion 9.86 R⊙ and aphelion 2 AU (period 1 year). Probe B: Earth–Jupiter ellipse with perihelion 1 AU and aphelion 5.2 AU (period 5.46 years).

Per year of coordinate time, the slowdown rates are:

- Probe A: 467.4 ms/yr (intermediate between perihelion-near-Sun and aphelion-at-2-AU regimes)
- Earth surface: 489.2 ms/yr
- Probe B: 150.8 ms/yr

This produces a counterintuitive result: Probe A, although diving close to the Sun, ages more than Earth on net, because Kepler's second law forces it to spend most of its orbit at low-dilation aphelion. Only an idealized circular orbit at perihelion would invert this. The mutual offset is therefore dominated by Probe B's larger separation from Earth.


Each probe relative to Earth
Probe A (Sun-grazer) − Earth
Probe B (Outer) − Earth
Earth (reference)
Gap between A and B
Clock difference vs Earth (ms)
Mission duration (Earth years)
Direct dilation between the two probes
Probe B − Probe A
B clock − A clock (ms)
After 50 yr:
15830 ms = 15.83 s
Mission duration (Earth years)

Figure 3. Three-twin paradox. Left: each probe's clock drift relative to Earth as a function of mission duration; the shaded region indicates the gap between the probes. Right: direct mutual offset, Probe B − Probe A.

5.3 Mission outcomes

At first natural rendezvous (one full Probe B orbit, ~5.46 years): A's clock 119 ms behind Earth, B's clock 1,848 ms ahead, mutual gap 1,729 ms. Over a 50-year mission: A behind Earth by 1.09 s, B ahead by 16.92 s, mutual gap of 15.83 seconds. This represents the maximum mutual dilation achievable between two chemically-propelled spacecraft within current power-system lifetimes.

6. Synchronization Architecture

6.1 The dual-clock principle

Time serves two distinct functions: sequencing local events (when does my heart beat, when does sunrise occur) and coordinating across observers (when did event X happen relative to event Y in a frame both observers can agree on). On Earth, both functions are served by a single clock because all observers share approximately the same gravitational potential and orbital frame; the dilation budget is below detection threshold for most civil purposes. Across planets, the functions separate.

We therefore propose a dual-clock architecture at every node:

- Civil clock: local proper time τ, defined by the local atomic clock ensemble. Drives biology, daily schedules, day/night cycle, life support. Tied to the body's rotation (UTC for Earth, MTC for Mars, lunar cycles for Moon, etc.).
- Coordinate clock: TCB (Barycentric Coordinate Time), generated locally by the relation $TCB = \tau / (1 - S(t))$. Used for all inter-node communication, distributed systems, scientific timestamps, and navigation.

Crucially, the coordinate clock is not a separate physical device. It is generated by applying a known scaling factor (continuously updated from local position and velocity) to the same atomic clock that drives the civil clock. The factor $S(t)$ varies on orbital timescales (hours to years) and is computed from onboard ephemerides.

6.2 Local TCB realization (Layer 1)

Each colony continuously produces its own local TCB estimate without requiring inter-node communication. The recipe at each node:

- Atomic clock ensemble produces local proper time τ (typically a Kalman-filtered weighted average of multiple cesium or optical lattice clocks).
- Onboard ephemeris provides position and velocity in solar-system coordinates.
- $S(t)$ is computed from gravitational potential and velocity contributions.
- TCB output: $\tau \times 1/(1 - S(t))$.

Modern optical lattice clocks achieve ~10^{-18} fractional stability; over a single day this translates to ~0.1 ns drift, well below the precision needed for navigation. Layer 1 alone provides autonomous, sub-nanosecond TCB to each colony.

6.3 Inter-node sync via Relativistic Two-Way Time Transfer (Layer 2)

Imperfect ephemerides and clock noise cause autonomous TCB realizations to drift apart. Layer 2 corrects this using a two-way exchange:

- Step 1: Node A sends timestamped packet at TCB time T_1, including its position $P\_A(T_1)$.
- Step 2: Light propagates along a null geodesic through curved spacetime. Travel time is computed including the Shapiro delay correction $\Delta t\_S = (2GM_\odot/c^3) \ln(4\, r\_A\, r\_B / b^2)$, where b is the impact parameter for the path past the Sun.
- Step 3: Node B receives at its TCB estimate T_2, immediately replies at T_3 with all four timestamps.
- Step 4: Node A receives at T_4. Using the standard NTP-style estimator: offset = $((T_2 - T_1) + (T_3 - T_4)) / 2$. The symmetric path cancels the light-time delay, leaving only the true clock offset.

The technique recovers nanosecond-class clock offsets despite multi-minute light delays. Verified numerically: a 50 ns true offset between Earth and Mars at opposition (4.32 min light time) is recovered exactly by the formula.

6.4 Achievable precision and the position-limited regime

The dominant error term in inter-node sync is not clock noise but position uncertainty: every meter of uncertainty in the position of either endpoint contributes 3.3 ns of timing error. The full error budget per sync cycle:

Error source	Magnitude
Atomic clock stability over 40 min	~2 ps
Ephemeris position uncertainty (~100 m)	~0.3 ns
Shapiro delay model uncertainty	< 1 ns
Solar plasma dispersion (Ka-band/optical)	< 0.1 ns
Tropospheric calibration (surface stations)	~ns
Total achievable per cycle	**~1 ns**

Table 3. Inter-node synchronization error budget. The system is in the position-limited regime: clocks are not the bottleneck.

7. Extension to Ships in Transit

A static colony has a position–velocity trajectory that is highly predictable from ephemeris models. A ship in transit does not: its position depends on commanded thrust, course corrections, and gravitational maneuvers. The slowdown factor S_ship(t) must be computed in real time from measured trajectory rather than read from a precomputed table. This couples timing and navigation in a way that requires joint estimation.

7.1 The triangle: origin, ship, destination

Three nodes: two static colonies (anchor pair) and one moving ship (challenger). The colonies are mutually synchronized via Layer 2 RTWTT and form a stable TCB anchor. The ship synchronizes to both anchors simultaneously, exploiting the geometric overdetermination to pin down both its position and its clock offset jointly.


Three-Node TCB Synchronization Architecture
EARTH (Origin)
Atomic clock ensemble
Local civil time (UTC)
Ephemeris: known
S_E ~ 14.88 ppb
~2 min light (varies)
SHIP (Challenger)
Atomic clock + IMU
S_ship(t) computed live
from measured trajectory
Dual-anchor TWTT
~2 min light (varies)
MARS (Destination)
Atomic clock ensemble
Local civil time (MTC)
Ephemeris: known
S_M ~ 9.68 ppb
Earth–Mars mutual TWTT (anchor pair) — 4–22 min light
DUAL-CLOCK PRINCIPLE (every node)
• Civil clock: local proper time τ — drives biology, schedules, day/night cycle (UTC, MTC, ship-day)
• Coordinate clock: TCB = τ × 1/(1−S(t)) — drives all inter-node communication & timestamps
• Static nodes: S(t) from ephemeris; Ship: S(t) measured live from IMU + nav fixes
• TWTT formula: clock offset = ((T₂ − T₁) + (T₃ − T₄)) / 2 — symmetric path cancels light delay
ACHIEVABLE PRECISION
• Atomic clocks (optical lattice): ~10⁻¹⁸ stability → sub-ns drift over hours
• Position-limited regime: 1 m position uncertainty ≡ 3.3 ns timing uncertainty
• Per sync cycle: ~1 ns achievable (Earth–Moon demonstrated; same architecture for Mars/Titan)

Figure 4. Three-node TCB synchronization architecture. The two anchor colonies form a stable mutual-sync pair; the ship dynamically estimates its own state via dual-anchor RTWTT and an Extended Kalman Filter.

7.2 Onboard algorithm

Aboard the ship, four phases run continuously:

- Phase A — Inertial dead reckoning: an inertial measurement unit (IMU) integrates proper acceleration to produce local position and velocity estimates. S_ship(t) is updated each cycle from these estimates plus the known potential model of the solar system.
- Phase B — Dual-anchor RTWTT: the ship periodically exchanges timestamped packets with both Earth and Mars (or any other anchor pair). Each exchange yields four timestamps and an independent estimate of the ship's clock offset against that anchor.
- Phase C — Extended Kalman Filter: position (3 DoF), velocity (3 DoF), clock offset (1), and clock drift rate (1) are jointly estimated as eight unknowns. Two independent four-timestamp constraints per cycle provide ample observability. Process model includes Newtonian gravity, commanded thrust profile, and post-Newtonian GR corrections; observation model includes light-time, Shapiro delay, and transponder turnaround delays.
- Phase D — Display and dissemination: civil time τ_ship drives crew life and engineering schedules; TCB drives all communication, science instruments, and navigation logs.

7.3 Worked example: midway through Earth–Mars transit

Consider a ship at heliocentric distance 1.25 AU, traveling at 35 km/s. Its slowdown decomposes as:

Component	Slowdown (ppb)
Sun's gravitational potential at 1.25 AU	7.90
Heliocentric kinematic (35 km/s)	6.82
Total ship slowdown vs TCB	**14.71**

Table 4. Slowdown decomposition for a ship in mid-transit, with Earth (14.88 ppb) and Mars (9.68 ppb) as anchor references. The ship sits dimensionally between the two anchors, providing favorable geometry for dual-anchor sync.

7.4 Sync cadence and special cases

Different mission phases require different sync rates: cruise phase tolerates hourly cycles; approach to destination requires several per minute; thrust events require continuous integration with explicit thrust modeling. During solar conjunctions, where the signal path passes near the Sun, Shapiro delay grows to ~124 μs and solar plasma scattering degrades precision; the standard fallback is single-anchor sync against the unobstructed colony, with the ship's autonomous Layer 1 realization bridging the conjunction window. Mars orbiters already follow this protocol routinely.

7.5 The Rindler effect during thrust

A non-inertial ship under thrust experiences differential dilation between clocks at different positions in the ship: $\Delta t/t \approx a\,L / c^2$. For electric propulsion (≤1 mg) on a 100 m ship the effect is ~10^{-17}, negligible. For chemical thrust at 5 g, the effect reaches 5×10^{-14} (~50 fs across the ship per second of burn) — measurable in principle but well below practical synchronization noise floors. Continuous-thrust regimes with high acceleration would require designating a single ship-reference clock and steering others; this is well-understood and not problematic in current mission classes.

8. Generalization and Discussion

The architecture as developed has a clean structural property: a ship is just a colony whose orbit is being measured rather than predicted. The same protocol applies to ground vehicles on Mars, drones in Titan's atmosphere, free-flying probes, and outer-system spacecraft. The only parameters that change between node classes are: how rapidly S(t) varies, how accurately position is known, and how frequently RTWTT must run to maintain accuracy. The physics and the protocol are invariant.

8.1 Why the system works

Three structural principles make this work, and they are worth stating explicitly:

- Dilation is not an obstacle but a known parameter. Once the slowdown factor S(t) is computed at each node, all relativistic effects appear as fixed (or slowly varying) scaling factors. The engineering reduces to applying these factors and exchanging timestamps.
- Symmetric paths cancel light delay. The two-way time transfer formula recovers clock offsets despite arbitrary light-time delays, provided the forward and reverse signal paths are geometrically symmetric. This is a 1960s technique; we are simply applying it at planetary scales.
- Joint estimation handles coupled unknowns. When position, velocity, and clock state are mutually dependent, an Extended Kalman Filter with sufficient observations decouples them automatically. This is the same principle that makes GPS work for moving receivers, scaled to planetary distances.

8.2 What the system does and does not provide

The architecture provides:

- Sub-nanosecond agreement on TCB across all nodes, sufficient for centimeter-class navigation and microsecond-class causal ordering.
- A single coordinate-time scale used by all machines, eliminating multi-zone translation layers.
- A clean separation of human-facing civil time from machine-facing coordinate time, mirroring how UTC and TT already coexist on Earth.

The architecture explicitly does not provide:

- A shared "now" across the solar system. There is no instantaneous shared present; this is a feature of relativistic spacetime, not an engineering shortfall.
- Faster-than-light coordination. Inter-node messages always carry minimum latencies of light-time. Distributed databases must accept causal-order semantics rather than wall-clock simultaneity.
- A monotonic global clock for low-latency distributed locks. TCB is monotonic but the latency to read it remotely is large; logical clocks (Lamport timestamps) are layered on top of TCB for software-level ordering.

8.3 Political and standards considerations

The technical readiness of the framework substantially exceeds the diplomatic readiness. As of early 2026, multiple agencies have independent lunar time programs, and a NASA Coordinated Lunar Time (LTC) is being developed alongside an Asia-Pacific equivalent based on the LTE440 ephemeris algorithm released in late 2025. Without coordination, every joint mission will require translation layers between incompatible standards. The arguments for adopting TCB universally as the inter-node coordinate time scale are strong: it is already defined by IAU Resolution B1.3 (2000), it requires no political negotiation about which body’s clock is "primary,"

and it generalizes uniformly to any solar-system location. We recommend this as the architectural baseline.

9. Conclusions

We have presented a complete framework for clock synchronization in a multi-planetary civilization, integrating relativistic physics with practical engineering. The principal results are:

- Forward time dilation accessible to chemical-propulsion missions: ~470 ms per year (realistic), ~10 s per year (idealized), ~509 s over a 50-year Saturn V–class mission (idealized).
- Reverse dilation: bounded at 489 ms per year by Earth's own dilation budget; ~340 ms/yr achievable with current technology.
- Mutual dilation between two opposing probes: ~16 seconds over 50 years, larger than either probe's individual dilation against Earth.
- Synchronization architecture: dual clocks at every node (civil + coordinate), Layer 1 autonomous TCB realization, Layer 2 RTWTT for inter-node consistency, Kalman-filter joint estimation for moving nodes.
- Achievable precision: ~1 ns per sync cycle, position-limited rather than clock-limited; sufficient for centimeter-class navigation and microsecond-class causal ordering across the solar system.

The framework is not speculative. Every component has flight heritage: GPS satellites correct for relativistic effects continuously; the Deep Space Network operates RTWTT-equivalent protocols with current spacecraft; lunar laser ranging and the LTE440 ephemeris demonstrate sub-nanosecond TCB realization at the Moon. What we have done here is integrate these established techniques into a single architecture and verify that they extend uniformly from Earth-Moon scales to outer-solar-system scales.

We further note that the architecture is graceful under extension. Adding a new colony — say, on Europa or Ceres — requires only specifying the colony's ephemeris and atomic clock infrastructure; no protocol changes. Adding a new ship requires only the onboard navigation suite; the protocol is identical. The system is principled, presently feasible, and reduces multi-planet timekeeping to ordinary engineering once general-relativistic effects are accepted as known parameters rather than obstacles.

The remaining barrier is political: the absence of a universally adopted coordinate time scale. The technical case for TCB is unambiguous. The diplomatic work is left to others.

References

Hafele, J. C., & Keating, R. E. (1972). Around-the-world atomic clocks: Predicted and observed relativistic time gains. Science, 177(4044), 166–170.

Morris, M. S., & Thorne, K. S. (1988). Wormholes in spacetime and their use for interstellar travel. American Journal of Physics, 56(5), 395–412.

Morris, M. S., Thorne, K. S., & Yurtsever, U. (1988). Wormholes, time machines, and the weak energy condition. Physical Review Letters, 61(13), 1446–1449.

Visser, M. (1989). Traversable wormholes: Some simple examples. Physical Review D, 39(10), 3182–3184.

Deutsch, D. (1991). Quantum mechanics near closed timelike lines. Physical Review D, 44(10), 3197–3217.

Lloyd, S., et al. (2011). Closed timelike curves via post-selection: Theory and experimental test of consistency. Physical Review Letters, 106(4), 040403.

Ringbauer, M., et al. (2014). Experimental simulation of closed timelike curves. Nature Communications, 5, 4145.

Lobo, F. S. N. (2010). Closed timelike curves and causality violation. arXiv:1008.1127.

Luminet, J.-P. (2021). Closed timelike curves, singularities and causality. Universe, 7(12), 484.

IAU (2000). Resolutions B1.3 and B1.5 (definition of TCB, TCG, and transformation framework). 24th General Assembly, Manchester.

Petit, G., & Wolf, P. (2005). Relativistic theory for time comparisons: A review. Metrologia, 42(3), S138–S144.

Allan, D. W., & Weiss, M. A. (1980). Accurate time and frequency transfer during common-view of a GPS satellite. Proceedings of the 34th Annual Symposium on Frequency Control, 334–346.

Lamport, L. (1978). Time, clocks, and the ordering of events in a distributed system. Communications of the ACM, 21(7), 558–565.

Cerf, V., et al. (2007). Delay-Tolerant Networking Architecture. RFC 4838, IETF.

National Space Council (April 2024). Memorandum on Celestial Time Standardization. Executive Office of the President.

Purple Mountain Observatory (2025). LTE440: A Numerical Lunar Time Ephemeris. Astronomy & Astrophysics, in press.